



**THE NORTH WEST CHINA RESEARCH INSTITUTE  
OF ELECTRONIC EQUIPMENT (NWIEE)**

No.30, Zhangba Sanlu, Xian, China

Tel: 86 29 88779380/88779382 Fax: 86 29 88779380

E-mail: ibdnwiee@pub.xaonline.com

Web: www.nwiesatcom.com www.nwiee.com

**ISO9001  
Certified**

**NWIEE 6.2M ANTENNA IN KA BAND**



The model 39SA062-KA 4.5M antenna system is designed and manufactured by NWIEE with CAD, which can be applied to GEO satellite tracking station.

The backup structure for the reflector, the hub connecting, the main reflector with mount and the pedestal provides the guaranteed pointing accuracy required in Ka band operation.

Antenna system is characteristic of high gain, low side-lobe, low noise temperature, low cross polarization, capable for frequency reuse both in transmit and receive bands, high driving/control accuracy with angle position display in high resolution.

39SA062-KA antenna system meets the standard of CCIR-REC580, ITU.

**NWIEE 4.5M ANTENNA IN KA BAND**

**R.F. Specifications**

Item	Receive	Transmit
Diameter	6.2M	
Frequency in GHz	19.6 ~ 21.2	29.4 ~ 31.0
Sidelobe Pattern	First sidelobe level $\leq -14$ dB	
Gain (dBi)	$59.4 + 20\lg(f/20.4)$	$62.8 + 20\lg(f/30.2)$
Polarization	Cross Polarization	



**THE NORTH WEST CHINA RESEARCH INSTITUTE  
OF ELECTRONIC EQUIPMENT (NWIEE)**

No.30, Zhangba Sanlu, Xian, China

Tel: 86 29 88779380/88779382 Fax: 86 29 88779380

E-mail: ibdnwiee@pub.xaonline.com

Web: www.nwieesatcom.com www.nwiee.com

**ISO9001  
Certified**

Cross Polarization Isolation	≥35 dB ( axial direction )	
Noise Temperature ( LNA input )	140K ( 20° El Angle, Sunny, Breeze )	
VSWR	1.35:1	1.35:1
Power Capacity		500W
Port to Port Isolation (dB)	Tx-Rx≥85	
Feed Insertion Loss(dB)	Rx:≤1.2 ; Tx:≤0.8	
Feed Interfaces	WR - 42	WR - 28
<b>Mechanical Specifications</b>		
Pedestal Mode	Rotate platform	
Azimuth Travel Range	±170°	
Elevation Travel Range	0°~90°	
Polarization Travel Range	±90°	
Az/El Travel Rate	0.001°~0.5°/sec	
Pol Travel Rate	0.5°/sec	
Tracking Accuracy	1/10 Beam width	
Surface Accuracy	0.3mm ( R.M.S )	
<b>Environment Specifications</b>		
Operation wind	20-35m/s	
Survival wind	55m/s (Stow position )	
Ambient temperature	-40°C ~60°C (Outdoor Devices)	
Humidity	0%~100%	
Solar radiation	360 BTU/h/ft²	
Radial ice (Survival)	13mm ice thick in normal operation, 25mm ice thick undestroyed.	
Seism (survival)	0.3 G's (Horizontal), 0.15 G's (Vertical)	